

Tekniske data

Fluke EI-1623 Selective/Stakeless Clamp Set



Produktoversikt: Fluke EI-1623 Selective/Stakeless Clamp Set

The Selective/Stakeless clamp set is used along with the Fluke 1623-2 and 1625-2 to perform Selective and Stakeless testing. Selective testing means using one clamp along with earth ground stakes to provide earth ground loop resistance values for one earth ground electrode. Stakeless testing uses both clamps provided to perform earth ground loop resistance measurement without stakes. Both tests have the advantage of providing measurements with no disconnection from the grounding system! Safer and quicker. Already included in the Fluke 1623-2 and 1625-2 kits. Both clamps have a 50.8 mm (2-inch) inner diameter.



Modeller



Fluke EI-1623

Fluke EI-1623 Selective/Stakeless Clamp Set



Fluke. Keeping your world up and running.®

Fluke Norge AS Postboks 383 1411 Kolbotn Tlf: 800 18 227 E-mail: cs.no@fluke.com www.fluke.no ©2022 Fluke Corporation. Med enerett. Informasjonen kan endres uten varsel. Vi tar forbehold om trykkfeil. 05/2022

Endring av dette dokumentet er ikke tillatt uten skriftlig tillatelse fra Fluke Corporation.